


**Re-Bo**
**Stainless steel circular saw blade medium, Ø×thickness: 350X3 mm**


## Order data

Order number	177520 350X3
GTIN	4045197245380
Item class	17B

## Description

### Version:

Precision toothings and very fine ground side faces. **Rake angle especially for stainless steels.**

**Nitrided surface:** hard, durable protection against edge build-up.

### Application:

**Pitch t:** (tooth form)

- **3 mm (BW)** – For thin pipes, profiles, sheet metal with 1 – 2 mm wall thickness.
- **4 mm (BW)** – For pipes, profiles, sheet metal with 1.5 – 4 mm wall thickness.
- **6 mm (HZ)** – For pipes, profiles and solid material above 4 mm wall thickness or cross-section up to a maximum of. 50 mm.
- **8 mm (HZ)** – For solid material above 50 mm.

### Suitable for :

**EISELE** and **TRENNJAEGER** cold circular saws.

### Note:

- **For optimum performance and service life: use coolant concentrate No. 084260.**
- **The concentricity and axial run-out values are considerably better than the figures according to DIN 1840, in some cases by up to 50 %.**

Tool material: HSS E

Thickness: 3 mm

Bore Ø: 40 mm

No. of teeth Z: 180

Pitch t: 6 mm  
Number of drive holes: 2; 4  
Drive hole Ø: 9; 12 mm

---

## Technical description

Thickness	3 mm
Bore Ø	40 mm
Ø	350 mm
Pitch t	6 mm
No. of teeth Z	180
Number of drive holes	2; 4
Drive hole Ø	9; 12 mm
Drive hole pitch circle	55; 64 mm
Tool material	HSS E
Type of product	Circular saw blade