

# Solid carbide circular saw blade DIN 1837 A fine, uncoated, $\emptyset \times$ thickness: 20X0,5 mm



### **Order data**

| Order number | 179800 20X0,5 |
|--------------|---------------|
| GTIN         | 4045197245823 |
| Item class   | 17C           |

## **Description**

#### Version:

Top quality German product with **precision toothing** and **hollow ground mirror finish sides**. Compared to HSS saw blades, the cutting speed can be increased by a factor of 3 to 4. **DIN 1837 A fine-toothed** with **raked teeth to form A** with chisel edge. **For thin-walled components and small cutting depths.** 

## Note:

- Stable conditions of machine and component clamping are important prerequisites. If these conditions are disregarded the circular saw blade may break.
- The values for radial run-out and axial run-out are considerably better than the values specified in DIN 1840.
- · Special sizes on request.

Standard: DIN 1837 Thickness: 0.5 mm Bore Ø: 5 mm No. of teeth Z: 50

## **Technical description**

| Thickness       | 0.5 mm             |
|-----------------|--------------------|
| Ø               | 20 mm              |
| Bore Ø          | 5 mm               |
| No. of teeth Z  | 50                 |
| Coating         | uncoated           |
| Tool material   | Solid carbide      |
| Standard        | DIN 1837           |
| Type of product | Circular saw blade |