

# Solid carbide circular saw blade DIN 1838 B coarse, uncoated, $\emptyset \times$ thickness: 30X0,25 mm



## **Order data**

Order number	179820 30X0,25
GTIN	4045197246790
Item class	17C

# **Description**

#### **Version:**

Top quality German product with **precision toothing** and **hollow ground mirror finish sides**. Compared to HSS saw blades, the cutting speed can be increased by a factor of 3 to 4. **DIN 1838 B coarse-toothed** with **curved teeth to form B** with chisel edge. **For cutting larger cross sections and greater cutting depths.** These blades are suitable for more universal use due to the improved chip formation and larger gullets compared to the fine-toothed version.

### Note:

- Stable conditions of machine and component clamping are important prerequisites. If these conditions are disregarded the circular saw blade may break.
- The values for radial run-out and axial run-out are considerably better than the values specified in DIN 1840.
- · Special sizes on request.

Standard: DIN 1838 Thickness: 0.25 mm Bore Ø: 8 mm No. of teeth Z: 40

# **Technical description**

Thickness	0.25 mm
Ø	30 mm
Bore Ø	8 mm
No. of teeth Z	40
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 1838
Type of product	Circular saw blade