

Garant
Circular saw blade, TiAlN, Ø×thickness: 63X2 mm

Order data

Order number	179912 63X2
GTIN	4045197938008
Item class	17C

Description
Version:

Optimised geometry and coating. Extra deep relief ground for reliable chip evacuation. For flat base of the slot.

Note:

- **Tooth profile BW.**
- **The tolerances for the circular saw blade diameter are considerably better than the values permissible to DIN 1837/1838, in some cases by up to 50%.**

Tool material: HSS

Thickness: 2 mm

Collar thickness E: 2.5 mm

maximum cutting depth $a_{e,max}$: 14 mm

Hub Ø: 32 mm

Bore Ø: 16 mm

No. of teeth Z: 24

Technical description

Collar thickness E	2.5 mm
--------------------	--------

Feed f_z in short-chipping aluminium	0.01 mm
Ø	63 mm
Thickness	2 mm
Bore Ø	16 mm
Hub Ø	32 mm
maximum cutting depth $a_{e\max}$	14 mm
No. of teeth Z	24
suitable adapter	179907 63; 80; 100
Drive hole pitch circle	25.5 mm
Drive hole Ø	4.4 mm
Number of drive holes	4
Coating	TiAlN
Tool material	HSS
Type of product	Circular saw blade