

**Garant**
**Narrow side milling cutter, uncoated, Ø×width js16×k11: 100X3,5 mm**


## Order data

Order number	185500 100X3,5
GTIN	4045197097569
Item class	11U

## Description

### Version:

**Circular milling cutter, cutting on three faces**, with bore collar and keyway. The alternate helical tooth pattern ensures smooth cutting, even on deep cuts.

### Application:

For **slotting or cutting-off** when the side faces of the component must have an accurate and clean surface.

### Note:

$f_z$  for  $a_e = 0.1 \times D$ .

Through-coolant: no

Bore Ø H7: 32 mm

No. of teeth Z: 36

Feed  $f_z$  in steel < 750 N/mm<sup>2</sup>: 0.06 mm

## Technical description

Feed $f_z$ in steel < 750 N/mm <sup>2</sup>	0.06 mm
Cutting edge Ø $D_c$	100 mm

Cutting width	3.5 mm
No. of teeth Z	36
Bore Ø H7	32 mm
Shank type	with bore
Coating	uncoated
Tool material	HSS Co 5
Standard	DIN 1834 A
Milling profile	staggered teeth
Type	N
Tolerance nominal Ø	js16
Through-coolant	no
Colour ring	without
Type of product	Side milling cutter