

Narrow side milling cutter, uncoated, Øxwidth js16xk11: 125X3,5 mm



Order data

| Order number | 185500 125X3,5 |
|--------------|----------------|
| GTIN | 4045197097644 |
| Item class | 11U |

Description

Version:

Circular milling cutter, cutting on three faces, with bore collar and keyway. The alternate helical tooth pattern ensures smooth cutting, even on deep cuts.

Application:

For **slotting or cutting-off** when the side faces of the component must have an accurate and clean surface.

Note:

 f_z for $a_e = 0.1 \times D$. Through-coolant: no Bore \varnothing H7: 32 mm

No. of teeth Z: 40

Feed f_z in steel < 750 N/mm²: 0.09 mm

Technical description

| Cutting width | 3.5 mm |
|--|---------|
| Feed f_z in steel $< 750 \text{ N/mm}^2$ | 0.09 mm |

| Bore Ø H7 | 32 mm |
|-------------------------------|---------------------|
| Cutting edge Ø D _c | 125 mm |
| No. of teeth Z | 40 |
| Shank type | with bore |
| Coating | uncoated |
| Tool material | HSS Co 5 |
| Standard | DIN 1834 A |
| Milling profile | staggered teeth |
| Туре | N |
| Tolerance nominal Ø | js16 |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Side milling cutter |