

Garant
Side milling cutter, uncoated, Ø×width js16×k11: 160X14 mm

Order data

| | |
|--------------|---------------|
| Order number | 185820 160X14 |
| GTIN | 4045197098160 |
| Item class | 11U |

Description
Version:

Staggered teeth with collar and keyway.

Application:

For **slotting or cutting-off** when the side faces of the component must have an accurate and clean surface.

Note:

f_z for $a_e = 0.1 \times D$.

Through-coolant: no

Bore Ø H7: 40 mm

No. of teeth Z: 22

Feed f_z in steel < 750 N/mm²: 0.11 mm

Technical description

| | |
|----------------|-------|
| Bore Ø H7 | 40 mm |
| Cutting width | 14 mm |
| No. of teeth Z | 22 |

| | |
|--|---------------------|
| Cutting edge $\varnothing D_c$ | 160 mm |
| Feed f_z in steel $< 750 \text{ N/mm}^2$ | 0.11 mm |
| Shank type | with bore |
| Coating | uncoated |
| Tool material | HSS Co 5 |
| Standard | DIN 885 A |
| Milling profile | staggered teeth |
| Type | N |
| Tolerance nominal \varnothing | js16 |
| Through-coolant | no |
| Colour ring | without |
| Type of product | Side milling cutter |