

Garant
Slot drill HSS-Co8, uncoated, Ø e8 DC: 11 mm

Order data

| | |
|--------------|---------------|
| Order number | 191000 11 |
| GTIN | 4045197099044 |
| Item class | 11W |

Description
Version:

Centre cutting edge geometry for plunging.

Application:

For milling **keyways** (slots) or pockets from the centre of the component.

Number of effective teeth Z (peripheral side): 2

Flute length L_c : 13 mm

Overall length L: 70 mm

Shank $\varnothing D_s$: 12 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.032 mm

Technical description

| | |
|--------------------------------------------------------------|-----------|
| Cutting edge $\varnothing D_c$ | 11 mm |
| Feed f_z for slot milling in steel < 750 N/mm ² | 0.032 mm |
| Number of effective teeth Z (peripheral side) | 2 |
| Shank $\varnothing D_s$ | 12 mm |
| Flute length L_c | 13 mm |
| Overall length L | 70 mm |
| Coating | uncoated |
| Tool material | HSS Co 8 |
| Standard | DIN 327 D |
| Type | N |

| | |
|---------------------------------|----------------------------------|
| Tolerance nominal \varnothing | e8 |
| Helix angle | 30 degrees |
| Direction of infeed | horizontal, oblique and vertical |
| Shank | DIN 1835 B to h6 |
| Through-coolant | no |
| Shank tolerance | h6 |
| Corner chamfer angle | 90 degrees |
| Colour ring | without |
| Type of product | End mill |