

Garant
Slot drill HSS-Co8, uncoated, Ø e8 DC: 13,7 mm

Order data

Order number	191000 13,7
GTIN	4045197099099
Item class	11W

Description
Version:

Centre cutting edge geometry for plunging.

Application:

For milling **keyways** (slots) or pockets from the centre of the component.

Number of effective teeth Z (peripheral side): 2

Flute length L_c : 16 mm

Overall length L: 73 mm

Shank $\varnothing D_s$: 12 mm

Feed f_z for slot milling in steel $< 750 \text{ N/mm}^2$: 0.038 mm

Technical description

Number of effective teeth Z (peripheral side)	2
Cutting edge $\varnothing D_c$	13.7 mm
Feed f_z for slot milling in steel $< 750 \text{ N/mm}^2$	0.038 mm
Shank $\varnothing D_s$	12 mm
Flute length L_c	16 mm
Overall length L	73 mm
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 327 D
Type	N

Tolerance nominal \varnothing	e8
Helix angle	30 degrees
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill