

**Garant**
**Slot drill HSS-Co8, uncoated, Ø e8 DC: 40 mm**

**Order data**

Order number	191000 40
GTIN	4045197099334
Item class	11W

**Description**
**Version:**

Centre cutting edge geometry for plunging.

**Application:**

For milling **keyways** (slots) or pockets from the centre of the component.

Number of effective teeth Z (peripheral side): 2

Flute length  $L_c$ : 38 mm

Overall length L: 130 mm

Shank Ø  $D_s$ : 32 mm

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.072 mm

**Technical description**

Cutting edge Ø $D_c$	40 mm
Number of effective teeth Z (peripheral side)	2
Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.072 mm
Shank Ø $D_s$	32 mm
Flute length $L_c$	38 mm
Overall length L	130 mm
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 327 D
Type	N

Tolerance nominal $\varnothing$	e8
Helix angle	30 degrees
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill