



## Slot drill HSS-Co8, N, Ø e8 DC: 3 mm



### Order data

Order number	191070 3
GTIN	4045197099709
Item class	12W

### Description

#### Version:

Centre cutting edge geometry for plunging.  
Economy version.

#### Application:

For milling **keyways** (slots) or pockets from the centre of the component.

Number of effective teeth Z (peripheral side): 2

Flute length  $L_c$ : 5 mm

Overall length L: 49 mm

Shank Ø  $D_s$ : 6 mm

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.007 mm

### Technical description

Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.007 mm
Cutting edge Ø $D_c$	3 mm
Number of effective teeth Z (peripheral side)	2
Shank Ø $D_s$	6 mm
Flute length $L_c$	5 mm
Overall length L	49 mm
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 327 D
Type	N

Tolerance nominal $\varnothing$	e8
Helix angle	30 degrees
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill