


**Slot drill HSS-Co8, N, Ø e8 DC: 7,5 mm**

**Order data**

Order number	191070 7,5
GTIN	4045197099822
Item class	12W

**Description**
**Version:**

Centre cutting edge geometry for plunging.  
Economy version.

**Application:**

For milling **keyways** (slots) or pockets from the centre of the component.

Number of effective teeth Z (peripheral side): 2

Flute length  $L_c$ : 10 mm

Overall length L: 60 mm

Shank Ø  $D_s$ : 10 mm

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.016 mm

**Technical description**

Cutting edge Ø $D_c$	7.5 mm
Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.016 mm
Number of effective teeth Z (peripheral side)	2
Shank Ø $D_s$	10 mm
Flute length $L_c$	10 mm
Overall length L	60 mm
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 327 D
Type	N

Tolerance nominal $\varnothing$	e8
Helix angle	30 degrees
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill