

Garant
Slot drill, W, Ø e8 DC: 20 mm

Order data

Order number	191100 20
GTIN	4045197100566
Item class	11W

Description
Version:

Centre cutting edge geometry for plunging. Wide, fine ground chip flutes. Exceptionally fine component surface finish - due to precisely ground cutting edges. For slots or for milling pockets from the component centre.

Note:

Note! Only for use in climb milling.

Number of effective teeth Z (peripheral side): 2

Flute length L_c : 38 mm

Overall length L: 104 mm

Shank $\varnothing D_s$: 20 mm

Feed f_z for slot milling in short-chipping aluminium: 0.055 mm

Technical description

Feed f_z for slot milling in short-chipping aluminium	0.055 mm
Cutting edge $\varnothing D_c$	20 mm
Number of effective teeth Z (peripheral side)	2
Shank $\varnothing D_s$	20 mm
Flute length L_c	38 mm
Overall length L	104 mm
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 844 B

Type	W
Tolerance nominal \varnothing	e8
Helix angle	42 degrees
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	yellow
Type of product	End mill