


**Mini slot drill HSS-PM, TiAlN, Ø e8 DC: 9,5 mm**

**Order data**

Order number	191380 9,5
GTIN	4045197102409
Item class	12W

**Description**
**Version:**

Centre cutting teeth for plunging.

**Eccentric relief ground.** Shank similar to DIN 1835 B with shank tolerance h6. General-purpose cutting edge geometry. For use as **slot drill or end mill** in side lock arbors and collet chucks.

**High cutting performance,** very competitive price. For milling keyways.

For the most demanding metal removal rates.

**Note:**

Save the regrinding costs: it is cheaper to use a mini slot drill to the limit of wear and throw it away, than to regrind it.

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: HB with h6

No. of teeth Z: 3

Flute length  $L_c$ : 11 mm

Overall length L: 48 mm

Shank Ø  $D_s$ : 10 mm

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.018 mm

**Technical description**

No. of teeth Z	3
Cutting edge Ø $D_c$	9.5 mm

Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.018 mm
Shank $\varnothing D_s$	10 mm
Overall length L	48 mm
Flute length $L_c$	11 mm
Direction of infeed	horizontal, oblique and vertical
Shank	HB with h6
Tolerance nominal $\varnothing$	e8
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	HSS PM
Standard	Manufacturer's standard
Type	N
Through-coolant	no
Colour ring	without
Type of product	End mill