

Garant
End mill, uncoated, Ø k10 DC: 14 mm

Order data

Order number	191530 14
GTIN	4045197103420
Item class	11W

Description
Version:

Multi-flute end mill. End face recessed.

Eccentric relief ground.

Through-coolant: no

Tolerance nominal Ø: k10

No. of teeth Z: 5

Helix angle: 30 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 1835 B to h6

No. of teeth Z: 5

Flute length L_c : 53 mm

Overall length L: 110 mm

Shank Ø D_s : 12 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.04 mm

Technical description

Feed f_z for slot milling in steel < 750 N/mm ²	0.04 mm
Cutting edge Ø D_c	14 mm
No. of teeth Z	5
Shank Ø D_s	12 mm
Overall length L	110 mm
Flute length L_c	53 mm
Direction of infeed	horizontal and oblique

Shank	DIN 1835 B to h6
Tolerance nominal Ø	k10
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 844 B
Type	N
Through-coolant	no
Colour ring	without
Type of product	End mill