

Garant
End mill, uncoated, Ø k10 DC: 40 mm

Order data

Order number	191530 40
GTIN	4045197103543
Item class	11W

Description
Version:

Multi-flute end mill. End face recessed.

Eccentric relief ground.

Through-coolant: no

Tolerance nominal Ø: k10

No. of teeth Z: 7

Helix angle: 30 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 1835 B to h6

No. of teeth Z: 7

Flute length L_c : 125 mm

Overall length L: 217 mm

Shank Ø D_s : 32 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.06 mm

Technical description

Cutting edge Ø D_c	40 mm
No. of teeth Z	7
Feed f_z for slot milling in steel < 750 N/mm ²	0.06 mm
Shank Ø D_s	32 mm
Overall length L	217 mm
Flute length L_c	125 mm
Direction of infeed	horizontal and oblique

Shank	DIN 1835 B to h6
Tolerance nominal Ø	k10
Helix angle	30 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 844 B
Type	N
Through-coolant	no
Colour ring	without
Type of product	End mill