

Garant
End mill HSS-PM, TiAlN, Ø k10 DC: 8 mm

Order data

Order number	191581 8
GTIN	4045197973764
Item class	11W

Description
Version:

Multi-flute end mill, for highest metal removal rate demands. Centre cutting edge geometry for plunging. **Eccentric relief ground**. For peripheral milling as a finishing operation, **producing very high surface finish quality**.

Advantage:

Excellent results when **milling dry**.

Through-coolant: no

Tolerance nominal Ø: k10

No. of teeth Z: 4

Helix angle: 50 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length L_c : 19 mm

Overall length L: 69 mm

Shank Ø D_s : 10 mm

Corner chamfer width at 45°: 0.2 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.024 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Corner chamfer width at 45°	0.2 mm
Tolerance nominal Ø	k10
Shank	DIN 1835 B to h6

Helix angle	50 degrees
Feed f_z for slot milling in steel < 750 N/mm ²	0.024 mm
Shank $\varnothing D_s$	10 mm
Cutting edge $\varnothing D_c$	8 mm
No. of teeth Z	4
Overall length L	69 mm
Flute length L_c	19 mm
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS PM
Standard	DIN 844 B
Type	N
Through-coolant	no
Colour ring	without
Type of product	End mill