


**Garant**
**End mill HSS-E-SPM HPC, TiAlN, Ø k10 DC: 10 mm**

**Order data**

Order number	191632 10
GTIN	4045197199010
Item class	11W

**Description**
**Version:**

Special **SPM** substrate with very high cobalt content.

Combines the **hardness of solid carbide** and the **toughness of PM steel**.

Dimensions to DIN 327.

**Advantage:**

This end mill can be used on a wide range of materials due to the universal geometry.

Tolerance nominal Ø: k10

No. of teeth Z: 4

Helix angle: 25 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length  $L_c$ : 13 mm

Overall length L: 63 mm

Shank Ø  $D_s$ : 10 mm

Feed  $f_z$  for side milling in steel < 1100 N/mm<sup>2</sup>: 0.019 mm

**Technical description**

No. of teeth Z	4
Cutting edge Ø $D_c$	10 mm
Feed $f_z$ for side milling in steel < 1100 N/mm <sup>2</sup>	0.019 mm
Shank Ø $D_s$	10 mm
Overall length L	63 mm

Flute length $L_c$	13 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal $\varnothing$	k10
Helix angle	25 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	HSS E SPM
Standard	DIN 327
Type	N
Helix angle characteristic	unequal spacing
Cutting width $a_e$ for milling operation	0.5×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill