


Garant
End mill HSS-E-SPM HPC, TiAlN, Ø k10 DC: 8 mm

Order data

Order number	191632 8
GTIN	4045197359469
Item class	11W

Description
Version:

Special **SPM** substrate with very high cobalt content.

Combines the **hardness of solid carbide** and the **toughness of PM steel**.

Dimensions to DIN 327.

Advantage:

This end mill can be used on a wide range of materials due to the universal geometry.

Tolerance nominal Ø: k10

No. of teeth Z: 4

Helix angle: 25 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length L_c : 11 mm

Overall length L: 61 mm

Shank Ø D_s : 10 mm

Feed f_z for side milling in steel < 1100 N/mm²: 0.012 mm

Technical description

Cutting edge Ø D_c	8 mm
No. of teeth Z	4
Feed f_z for side milling in steel < 1100 N/mm ²	0.012 mm
Shank Ø D_s	10 mm
Overall length L	61 mm

Flute length L_c	11 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	k10
Helix angle	25 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	HSS E SPM
Standard	DIN 327
Type	N
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill