




## End mill HSS-E-SPM HPC, TiAlN, Ø DC: 25 mm



### Order data

Order number	191637 25
GTIN	4045197838995
Item class	12W

### Description

#### Version:

Very high-performance substrate for machining steel and stainless steel materials.

Tolerance nominal  $\varnothing$ : 0 / -0.03

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length  $L_c$ : 45 mm

Overall length L: 121 mm

Shank  $\varnothing D_s$ : 25 mm

Feed  $f_z$  for side milling in steel < 1100 N/mm<sup>2</sup>: 0.08 mm

### Technical description

Tolerance nominal $\varnothing$	0 / -0.03
No. of teeth Z	4
Direction of infeed	horizontal, oblique and vertical
Overall length L	121 mm
Feed $f_z$ for side milling in steel < 1100 N/mm <sup>2</sup>	0.08 mm
Shank $\varnothing D_s$	25 mm
Shank	DIN 1835 B to h6
Flute length $L_c$	45 mm

Cutting edge $\varnothing D_c$	25 mm
Helix angle	38 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS E SPM
Standard	DIN 844 B
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill