

Garant
Semi-roughing end mill, uncoated, Ø k10 DC: 25 mm

Order data

Order number	191640 25
GTIN	4045197104410
Item class	11W

Description
Version:
Universal end mill with relief ground semi-roughing profile.

Centre cutting teeth for plunging.

Eccentric relief ground.

Universal cutting edge geometry.

Through-coolant: no

Tolerance nominal Ø: k10

No. of teeth Z: 3

Helix angle: 25 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 3

Flute length L_c : 45 mm

Overall length L: 121 mm

Shank Ø D_s : 25 mm

Corner chamfer width at 45°: 0.5 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.07 mm

Technical description

Feed f_z for slot milling in steel < 750 N/mm ²	0.07 mm
Corner chamfer width at 45°	0.5 mm
No. of teeth Z	3
Cutting edge Ø D_c	25 mm
Shank Ø D_s	25 mm

Overall length L	121 mm
Flute length L _c	45 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal Ø	k10
Helix angle	25 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	NF
Through-coolant	no
Colour ring	without
Type of product	End mill