

**Garant**
**Roughing end mill HSS-PM, TiAlN, Ø js12 DC: 8 mm**

**Order data**

Order number	192445 8
GTIN	4045197106070
Item class	11W

**Description**
**Version:**
**Relief ground knuckle form profile.**

Centre cutting teeth for plunging.

**Universal end mills** for profile milling or for plunging.

For the most demanding metal removal rates.

**Advantage:**

Compared to multi-flute cutters, **better chip evacuation due to larger flutes.**

Through-coolant: no

Tolerance nominal Ø: js12

No. of teeth Z: 3

Helix angle: 25 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 3

Flute length  $L_c$ : 19 mm

Overall length L: 69 mm

Shank Ø  $D_s$ : 10 mm

Corner chamfer width at 45°: 0.3 mm

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.015 mm

**Technical description**

Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.015 mm
Corner chamfer width at 45°	0.3 mm
No. of teeth Z	3

Cutting edge $\varnothing D_c$	8 mm
Shank $\varnothing D_s$	10 mm
Overall length L	69 mm
Flute length $L_c$	19 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal $\varnothing$	js12
Helix angle	25 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS PM
Standard	DIN 844 B
Milling profile	NR
Through-coolant	no
Colour ring	without
Type of product	End mill