

Garant
Roughing end mill HSS-Co8, uncoated, Ø js14 DC: 25 mm

Order data

Order number	192520 25
GTIN	4045197106735
Item class	11W

Description
Version:
Relief ground knuckle form profile.

Centre cutting teeth for plunging.

- **Wide, precision ground chip flutes.**
- **Special chip angle for aluminium and non-ferrous metals.**

Advantage:

Suitable **for high machining volumes** due to the large flutes.

Through-coolant: no

Tolerance nominal Ø: js14

No. of teeth Z: 3

Helix angle: 36 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 3

Flute length L_c : 90 mm

Overall length L: 166 mm

Shank Ø D_s : 25 mm

Corner chamfer width at 45°: 0.5 mm

Feed f_z for slot milling in short-chipping aluminium: 0.09 mm

Technical description

Feed f_z for slot milling in short-chipping aluminium	0.09 mm
Corner chamfer width at 45°	0.5 mm
Cutting edge Ø D_c	25 mm
No. of teeth Z	3

Shank $\varnothing D_s$	25 mm
Overall length L	166 mm
Flute length L_c	90 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	js14
Helix angle	36 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	WR
Through-coolant	no
Colour ring	yellow
Type of product	End mill