

Garant
Roughing end mill HSS-PM, TiAlN, Ø DC: 8M mm

Order data

Order number	192645 8M
GTIN	4045197107220
Item class	11W

Description
Version:
With relief ground knuckle form profile.

Up to size 20 with end cutting teeth profile for plunging.

The wide teeth lands permit multiple re-grinding without losing the profile.

HSS-PM – For highest demands on metal removal rates.

Sizes 6M to 25M – **MID mills:** dimensions to **factory standard, which is between DIN 844 stub and DIN 844 long.**

Through-coolant: no

Tolerance nominal Ø: js12

No. of teeth Z: 4

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length L_f : 28 mm

Overall length L: 78 mm

Shank Ø D_s : 10 mm

Corner chamfer width at 45°: 0.3 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.025 mm

Technical description

Corner chamfer width at 45°	0.3 mm
No. of teeth Z	4
Feed f_z for slot milling in steel < 750 N/mm ²	0.025 mm

Cutting edge $\varnothing D_c$	8 mm
Shank $\varnothing D_s$	10 mm
Overall length L	78 mm
Flute length L_c	28 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	js12
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS PM
Standard	DIN 844 B
Milling profile	NR
Through-coolant	no
Colour ring	without
Type of product	End mill