



Roughing end mill HSS-Co8, TiAlN, Ø DC: 12M mm



Order data

Order number	192650 12M
GTIN	4045197107541
Item class	12W

Description

Version:

With relief ground knuckle form profile.

Up to size 20 with end cutting teeth profile for plunging.

The wide teeth lands permit multiple re-grinding without losing the profile.

Sizes 6M to 25M – **MID mills:** dimensions to **factory standard, which is between DIN 844 stub and DIN 844 long.**

Economy version.

Through-coolant: no

Tolerance nominal Ø: js12

No. of teeth Z: 4

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length L_c : 40 mm

Overall length L: 97 mm

Shank Ø D_s : 12 mm

Corner chamfer width at 45°: 0.6 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.021 mm

Technical description

Corner chamfer width at 45°	0.6 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.021 mm
Cutting edge Ø D_c	12 mm

No. of teeth Z	4
Shank $\varnothing D_s$	12 mm
Overall length L	97 mm
Flute length L_c	40 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	js12
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	NR
Through-coolant	no
Colour ring	without
Type of product	End mill