



Roughing end mill HSS-Co8, TiAlN, Ø DC: 7 mm



Order data

Order number	192650 7
GTIN	4045197107466
Item class	12W

Description

Version:

With relief ground knuckle form profile.

Up to size 20 with end cutting teeth profile for plunging.

The wide teeth lands permit multiple re-grinding without losing the profile.

Sizes 6M to 25M – **MID mills:** dimensions to **factory standard, which is between DIN 844 stub and DIN 844 long.**

Economy version.

Through-coolant: no

Tolerance nominal Ø: js12

No. of teeth Z: 4

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length L_c : 16 mm

Overall length L: 66 mm

Shank Ø D_s : 10 mm

Corner chamfer width at 45°: 0.3 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.006 mm

Technical description

Cutting edge Ø D_c	7 mm
Corner chamfer width at 45°	0.3 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.006 mm

No. of teeth Z	4
Shank $\varnothing D_s$	10 mm
Overall length L	66 mm
Flute length L_c	16 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	js12
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	NR
Through-coolant	no
Colour ring	without
Type of product	End mill