

Garant
Roughing end mill, TiAlN, Ø DC: 25 mm

Order data

Order number	192710 25
GTIN	4045197107824
Item class	11W

Description
Version:
Relief ground knuckle form profile.

Up to size 20 end cutting teeth profile for plunging.

Through-coolant: no

Tolerance nominal Ø: k12

No. of teeth Z: 5

Helix angle: 27 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 1835 B to h6

No. of teeth Z: 5

Flute length L_c : 90 mm

Overall length L: 166 mm

Shank Ø D_s : 25 mm

Corner chamfer width at 45°: 0.5 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.06 mm

Technical description

Corner chamfer width at 45°	0.5 mm
Cutting edge Ø D_c	25 mm
No. of teeth Z	5
Feed f_z for slot milling in steel < 750 N/mm ²	0.06 mm
Shank Ø D_s	25 mm
Overall length L	166 mm

Flute length L_c	90 mm
Direction of infeed	horizontal and oblique
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	k12
Helix angle	27 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	NR
Spacing of the cutters	unequal spacing
Through-coolant	no
Colour ring	without
Type of product	End mill