

Garant
Roughing end mill, TiAlN, Ø DC: 7 mm

Order data

Order number	1927107
GTIN	4045197107916
Item class	11W

Description
Version:
Relief ground knuckle form profile.

Up to size 20 end cutting teeth profile for plunging.

Through-coolant: no

Tolerance nominal Ø: k12

No. of teeth Z: 4

Helix angle: 27 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length L_c : 30 mm

Overall length L: 80 mm

Shank Ø D_s : 10 mm

Corner chamfer width at 45°: 0.5 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.01 mm

Technical description

Cutting edge Ø D_c	7 mm
Feed f_z for slot milling in steel < 750 N/mm ²	0.01 mm
No. of teeth Z	4
Corner chamfer width at 45°	0.5 mm
Shank Ø D_s	10 mm
Overall length L	80 mm

Flute length L_c	30 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal \varnothing	k12
Helix angle	27 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	NR
Spacing of the cutters	unequal spacing
Through-coolant	no
Colour ring	without
Type of product	End mill