



## Roughing end mill, TiAlN, Ø DC: 20 mm



### Order data

Order number	192720 20
GTIN	4045197107992
Item class	12W

### Description

#### Version:

#### Relief ground knuckle form profile.

Up to size 20 end cutting teeth profile for plunging.

Economy version.

Through-coolant: no

Tolerance nominal Ø: js12

No. of teeth Z: 4

Helix angle: 27 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 1835 B to h6

No. of teeth Z: 4

Flute length  $L_c$ : 75 mm

Overall length L: 141 mm

Shank Ø  $D_s$ : 20 mm

Corner chamfer width at 45°: 0.6 mm

Feed  $f_z$  for slot milling in steel < 750 N/mm<sup>2</sup>: 0.06 mm

### Technical description

No. of teeth Z	4
Cutting edge Ø $D_c$	20 mm
Corner chamfer width at 45°	0.6 mm
Feed $f_z$ for slot milling in steel < 750 N/mm <sup>2</sup>	0.06 mm
Shank Ø $D_s$	20 mm
Overall length L	141 mm

Flute length L <sub>c</sub>	75 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 1835 B to h6
Tolerance nominal Ø	js12
Helix angle	27 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	HSS Co 8
Standard	DIN 844 B
Milling profile	NR
Through-coolant	no
Colour ring	without
Type of product	End mill