

Garant
Woodruff keyseating cutter, uncoated, \varnothing DC \times LC h11 \times e8: 25,5X5 mm

Order data

Order number	194010 25,5X5
GTIN	4045197109309
Item class	11W

Description
Version:

Peripheral cutting, alternate set teeth (staggered).

The sides of the teeth are ground to give clearance and thus cannot jam in the component.

Special surface treatment.

Note:

For milling Woodruff keyways to DIN 6888 or for milling small slots.

No. of teeth Z: 10

No. of teeth Z: 10

for Woodruff keyways to DIN 6888: 5,0 \times 10,0 mm

Overall length L: 63 mm

Shank \varnothing D_s: 10 mm

Feed f_z for slot milling in steel < 750 N/mm²: 0.08 mm

Technical description

Cutting edge \varnothing D _c	25.5 mm
for Woodruff keyways to DIN 6888	5,0 \times 10,0 mm
Feed f _z for slot milling in steel < 750 N/mm ²	0.08 mm
No. of teeth Z	10
Shank \varnothing D _s	10 mm
Overall length L	63 mm

Flute length L _c	5 mm
Coating	uncoated
Tool material	HSS Co 5
Standard	DIN 850 D/F
Milling profile	staggered teeth
Tolerance nominal Ø	e8
Direction of infeed	horizontal
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill