

Garant
T-slot cutter, uncoated, \varnothing DC \times LC d11 \times d11: 16X8 mm


Order data

Order number	194030 16X8
GTIN	4045197109545
Item class	11W

Description

Version:

The mill cuts on all three sides.

Due to alternate set teeth (staggered), high cutting performance is achieved.

Note:

For milling T-slots to DIN 650 into machine tables on jigs and fixtures.

No. of teeth Z: 6

No. of teeth Z: 6

for T-slots DIN 650: 8 mm

Recess \varnothing D₁: 7 mm

Overall length L: 62 mm

Shank \varnothing D_s: 10 mm

Feed f_z in steel < 750 N/mm²: 0.06 mm

Technical description

Feed f _z in steel < 750 N/mm ²	0.06 mm
for T-slots DIN 650	8 mm
Cutting edge \varnothing D _c	16 mm
No. of teeth Z	6
Recess \varnothing D ₁	7 mm
Shank \varnothing D _s	10 mm
Overall length L	62 mm

Flute length L _c	8 mm
Coating	uncoated
Tool material	HSS Co 5
Milling profile	staggered teeth
Tolerance nominal Ø	d11
Helix angle	15 degrees
Direction of infeed	horizontal
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill