

**Garant**
**T-slot cutter, uncoated, Ø DC × LC d11 × d11: 18X8 mm**


## Order data

Order number	194030 18X8
GTIN	4045197109552
Item class	11W

## Description

### Version:

The mill cuts on all three sides.

Due to alternate set teeth (staggered), high cutting performance is achieved.

### Note:

For milling T-slots to DIN 650 into machine tables on jigs and fixtures.

No. of teeth Z: 6

No. of teeth Z: 6

for T-slots DIN 650: 10 mm

Recess Ø D<sub>1</sub>: 8 mm

Overall length L: 70 mm

Shank Ø D<sub>s</sub>: 12 mm

Feed f<sub>z</sub> in steel < 750 N/mm<sup>2</sup>: 0.06 mm

## Technical description

for T-slots DIN 650	10 mm
Feed f <sub>z</sub> in steel < 750 N/mm <sup>2</sup>	0.06 mm
Cutting edge Ø D <sub>c</sub>	18 mm
No. of teeth Z	6
Recess Ø D <sub>1</sub>	8 mm
Shank Ø D <sub>s</sub>	12 mm
Overall length L	70 mm

Flute length L <sub>c</sub>	8 mm
Coating	uncoated
Tool material	HSS Co 5
Milling profile	staggered teeth
Tolerance nominal Ø	d11
Helix angle	15 degrees
Direction of infeed	horizontal
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill