

Garant
Dovetail milling cutter, form C 45°, uncoated, Ø js16 DC: 25 mm


Order data

Order number	194040 25
GTIN	4045197109637
Item class	11W

Description

Version:

Special surface treatment.
Form C cuts frontal and on the circumference.

Note:

For milling small dovetails in tool making and machine building.

Through-coolant: no

No. of teeth Z: 10

No. of teeth Z: 10

Recess Ø D₁: 8 mm

Overall length L: 67 mm

Shank Ø D_s: 12 mm

Flute length L_c: 6.3 mm

Feed f_z in steel < 750 N/mm²: 0.08 mm

Technical description

Cutting edge Ø D _c	25 mm
Recess Ø D ₁	8 mm
Feed f _z in steel < 750 N/mm ²	0.08 mm
No. of teeth Z	10
Shank Ø D _s	12 mm
Overall length L	67 mm

Flute length L _c	6.3 mm
Shape	C
Coating	uncoated
Tool material	HSS Co 5
Standard	DIN 1833
Tolerance nominal Ø	js16
Direction of infeed	horizontal
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	45 degrees
Colour ring	without
Type of product	End mill