

Garant
T-slot semi-roughing cutter, uncoated, \varnothing DC \times LC d11 \times d11: 25X11 mm


Order data

Order number	194050 25X11
GTIN	4045197109712
Item class	11W

Description

Version:

Cuts on all three sides.

Alternate set teeth with ground chip breaker on flutes.

Note:

For milling T-slots to DIN 650.

No. of teeth Z: 8

No. of teeth Z: 8

for T-slots DIN 650: 14 mm

Recess \varnothing D₁: 12 mm

Overall length L: 82 mm

Shank \varnothing D_s: 16 mm

Feed f_z in steel $< 750 \text{ N/mm}^2$: 0.08 mm

Technical description

Cutting edge \varnothing D _c	25 mm
for T-slots DIN 650	14 mm
Feed f_z in steel $< 750 \text{ N/mm}^2$	0.08 mm
No. of teeth Z	8
Recess \varnothing D ₁	12 mm
Shank \varnothing D _s	16 mm
Overall length L	82 mm

Flute length L _c	11 mm
Coating	uncoated
Tool material	HSS Co 5
Milling profile	staggered teeth
Tolerance nominal Ø	d11
Helix angle	15 degrees
Direction of infeed	horizontal
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	without
Type of product	End mill