

Garant
Dovetail milling cutter, form C 60°, uncoated, Ø js16 DC: 16 mm

Order data

Order number	194060 16
GTIN	4045197109767
Item class	11W

Description
Version:

Special surface treatment.
Form C cuts frontal and on the circumference.

Note:

For milling small dovetails in tool making and machine building.

Through-coolant: no

No. of teeth Z: 6

No. of teeth Z: 6

Recess Ø D₁: 6 mm

Overall length L: 60 mm

Shank Ø D_s: 12 mm

Flute length L_c: 6.3 mm

Feed f_z in steel < 750 N/mm²: 0.06 mm

Technical description

No. of teeth Z	6
Recess Ø D ₁	6 mm
Cutting edge Ø D _c	16 mm
Feed f _z in steel < 750 N/mm ²	0.06 mm
Shank Ø D _s	12 mm
Overall length L	60 mm

Flute length L _c	6.3 mm
Shape	C
Coating	uncoated
Tool material	HSS Co 5
Standard	DIN 1833
Tolerance nominal Ø	js16
Direction of infeed	horizontal
Shank	DIN 1835 B to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	60 degrees
Colour ring	without
Type of product	End mill