


**Solid carbide slot drill DIN 6535 HB, uncoated, Ø DC: 8 mm**

**Order data**

Order number	201280 8
GTIN	4045197112491
Item class	12X

**Description**
**Version:**

Stronger cutting edges.

Dimensions similar to DIN 6527.

Through-coolant: no

Tolerance nominal Ø: h10

No. of teeth Z: 2

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 2

Flute length  $L_c$ : 19 mm

Overall length L: 63 mm

Shank Ø  $D_s$ : 8 mm

Corner chamfer width at 45°: 0.1 mm

Feed  $f_z$  for slot milling in short-chipping aluminium: 0.03 mm

**Technical description**

No. of teeth Z	2
Feed $f_z$ for side milling in short-chipping aluminium	0.04 mm
Feed $f_z$ for slot milling in short-chipping aluminium	0.03 mm
Corner chamfer width at 45°	0.1 mm
Cutting edge Ø $D_c$	8 mm
Shank Ø $D_s$	8 mm

Overall length L	63 mm
Flute length L <sub>c</sub>	19 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal Ø	h10
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Cutting width a <sub>e</sub> for milling operation	0.5×D for side milling
Cutting width a <sub>e</sub> for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	yellow
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
------------------------	-------------