Garant

Solid carbide slot drill HPC, TiAIN, Ø DC: 0,5 mm



Order data

Order number	201648 0,5
GTIN	4045197641410
Item class	11X

Description

Version:

GARANT Diabolo 70:

Special solid carbide substrate with extremely high tensile strength combined with outstanding wear resistance for optimum process reliability. Newly developed nano-crystalline high-tech coating for hard milling up to 70 HRC. Very suitable for continuous use in tool and mould making.

Sizes 0.5 - 5: **Recess angle** $\alpha = 15^{\circ}$.

Application:

Due to the **special hard geometry** ideal for use on hardened materials from 60 HRC to 70 HRC. **Note:** f_z for $a_p = 0.05 \times D$.

Tolerance nominal \emptyset : 0 / -0.02 No. of teeth Z: 2 Helix angle: 35 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HA to h6 No. of teeth Z: 2 Flute length L_c: 1.3 mm Overall length L: 40 mm Shank \emptyset D_s: 4 mm Feed f_z for slot milling in steel < 70 HRC: 0.003 mm Feed f_z for side milling in steel < 70 HRC: 0.004 mm

Technical description

Feed f_z for slot milling in steel < 70 HRC	0.003 mm
No. of teeth Z	2

© Hoffmann GmbH Qualitätswerkzeuge

Cutting edge Ø D_c	0.5 mm
Feed f_z for side milling in steel < 70 HRC	0.004 mm
Shank Ø D _s	4 mm
Overall length L	40 mm
Flute length L _c	1.3 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal Ø	0 / -0.02
Helix angle	35 degrees
Corner chamfer angle	90 degrees
Series	Diabolo
Coating	TiAIN
Tool material	Solid carbide
Standard	Manufacturer's standard
Туре	Н
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.05×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	red
Type of product	End mill

Services

209900 FRST