

Garant
Solid carbide slot drill, DLC, Ø e8 DC: 3 mm

Order data

Order number	201735 3
GTIN	4045197746238
Item class	11X

Description
Version:

With the latest generation of **DLC coating sp²**.
Special geometry for machining aluminium and plastics.

Application:

Double relieved chip angle, **especially for aluminium machining.**

Through-coolant: no

Tolerance nominal Ø: e8

No. of teeth Z: 2

Helix angle: 20 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 2

Flute length L_c: 11 mm

Overhang length L₁ incl. recess: 14 mm

Recess Ø D₁: 2.8 mm

Overall length L: 50 mm

Shank Ø D_s: 3 mm

Technical description

Feed f _z for slot milling in cast aluminium	0.008 mm
Tolerance nominal Ø	e8
No. of teeth Z	2
Cutting edge Ø D _c	3 mm
Feed f _z for side milling in cast aluminium	0.01 mm

Direction of infeed	horizontal, oblique and vertical
Recess $\varnothing D_1$	2.8 mm
Overall length L	50 mm
Shank	DIN 6535 HA to h6
Overhang length L_1 incl. recess	14 mm
Shank $\varnothing D_s$	3 mm
Flute length L_c	11 mm
Helix angle	20 degrees
Corner chamfer angle	90 degrees
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Cutting width a_e for milling operation	0,25×D ved beskæring
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	yellow
Type of product	End mill