


**Solid carbide mini slot drill, TiAlN, Ø e8 DC: 10 mm**

**Order data**

Order number	201920 10
GTIN	4045197114969
Item class	12X

**Description**
**Version:**

**Double relief ground side clearance angle. Centre cutting teeth for plunging.**

Weldon shank **similar to DIN 6535 HB.**

**Note:**
**Save on regrinding costs:**

It is cheaper to use solid carbide mini slot drills to the wear limit than to regrind them.

Cutting width  $a_e$  for milling operation: Full slot cutting depth  $1 \times D$

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 3

Flute length  $L_c$ : 16 mm

Overall length L: 55 mm

Shank Ø  $D_s$ : 10 mm

Shank form: HB

Corner chamfer width at 45°: 0.05 mm

**Technical description**

No. of teeth Z	3
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.05 mm
Cutting edge Ø $D_c$	10 mm
Corner chamfer width at 45°	0.05 mm

Feed $f_z$ for side milling in steel $< 900 \text{ N/mm}^2$	0.06 mm
Shank form	HB
Shank $\varnothing D_s$	10 mm
Overall length L	55 mm
Flute length $L_c$	16 mm
Direction of infeed	horizontal, oblique and vertical
Correction factor for $v_c$	1.25
Shank	DIN 6535 HB to h6
Tolerance nominal $\varnothing$	e8
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Cutting width $a_e$ for milling operation	$0.5 \times D$ for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Colour ring	without
Type of product	End mill