



Solid carbide slot drill, uncoated, Ø e8 DC: 12 mm

Order data

Order number	202242 12
GTIN	4045197767158
Item class	12X

Description
Version:

Eccentric relief ground, additionally **finish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Application:

For roughing and finishing.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 3

Flute length L_c : 36 mm

Overall length L: 100 mm

Shank Ø D_s : 12 mm

Feed f_z for slot milling in short-chipping aluminium: 0.05 mm

Feed f_z for side milling in short-chipping aluminium: 0.07 mm

Technical description

Shank	DIN 6535 HA to h6
No. of teeth Z	3
Overall length L	100 mm
Direction of infeed	horizontal, oblique and vertical
Cutting edge Ø D_c	12 mm
Feed f_z for side milling in short-chipping aluminium	0.07 mm

Flute length L_c	36 mm
Feed f_z for slot milling in short-chipping aluminium	0.05 mm
Shank $\varnothing D_s$	12 mm
Tolerance nominal \varnothing	e8
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	yellow
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 12 mm	SZ2025 12
Shank grinding Type HB	129100 HB