Garant

Solid carbide milling cutter MTC, uncoated, Ø DC: 10M mm



Order data

Order number	202244 10M
GTIN	4045197654786
Item class	11X

Description

Version:

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Without 45° corner chamfer.

Without 45° corner chamfer.

Size 1-2 – tolerance: Size nominal \emptyset **D**_C = **e8.**

Size 2.5–20M – tolerance: Size nominal \emptyset **D**_c = **h6**.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres. **Note:**

NEW GENERATION AVAILABLE! Recommended successor product is No. 202002.

Tolerance nominal \emptyset : h6 No. of teeth Z: 3 Helix angle: 45 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HA to h6 Balance quality with shank: G 2.5 with HA No. of teeth Z: 3 Flute length L_c: 30 mm Overhang length L₁ incl. recess: 38 mm Recess \emptyset D₁: 9.2 mm Overall length L: 80 mm Shank \emptyset D_s: 10 mm

Technical description

Overhang length L₁ incl. recess

38 mm

Shank form	НА
Feed f_z for slot milling in short-chipping aluminium	0.04 mm
Cutting edge Ø D _c	10 mm
No. of teeth Z	3
Recess Ø D ₁	9.2 mm
Feed f_z for side milling in short-chipping aluminium	0.05 mm
Shank Ø D _s	10 mm
Overall length L	80 mm
Flute length L _c	30 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal Ø	h6
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST

209900 FRST

© Hoffmann GmbH Qualitätswerkzeuge

Shank grinding Type HB

129100 HB