

Garant
Solid carbide milling cutter MTC, uncoated, Ø h6 DC: 16 mm

Order data

Order number	202247 16
GTIN	4045197571076
Item class	11X

Description
Version:

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c : 25 mm

Overhang length L_1 incl. recess: 100 mm

Recess Ø D_1 : 15 mm

Overall length L: 150 mm

Shank Ø D_s : 16 mm

Technical description

Feed f_z for slot milling in short-chipping aluminium	0.065 mm
Shank form	HB
Recess Ø D_1	15 mm
Feed f_z for side milling in short-chipping aluminium	0.09 mm
Corner chamfer width at 45°	0.2 mm

Overhang length L_1 incl. recess	100 mm
Cutting edge $\varnothing D_c$	16 mm
No. of teeth Z	3
Shank $\varnothing D_s$	16 mm
Overall length L	150 mm
Flute length L_c	25 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	h6
Balance quality with shank	G 2.5 with HB
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16

