

Garant
Solid carbide milling cutter MTC, uncoated, Ø h6 DC: 8 mm

Order data

Order number	202247 8
GTIN	4045197571045
Item class	11X

Description
Version:

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 13 mm

Overhang length L_1 incl. recess: 62 mm

Recess Ø D_1 : 7.4 mm

Overall length L: 100 mm

Shank Ø D_s : 8 mm

Technical description

Feed f_z for side milling in short-chipping aluminium	0.04 mm
Cutting edge Ø D_c	8 mm
Corner chamfer width at 45°	0.2 mm
Shank form	HA
Feed f_z for slot milling in short-chipping aluminium	0.03 mm

Recess $\varnothing D_1$	7.4 mm
Overhang length L_1 incl. recess	62 mm
No. of teeth Z	3
Shank $\varnothing D_s$	8 mm
Overall length L	100 mm
Flute length L_c	13 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal \varnothing	h6
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB