

Garant
Solid carbide milling cutter HPC, ZOx, Ø f8 DC: 10 mm

Order data

| | |
|--------------|---------------|
| Order number | 202248 10 |
| GTIN | 4045197271556 |
| Item class | 11X |

Description
Version:

Sturdy roughing end mill **without** knuckle profile.

With strong core, **special chip breaker recesses** and **large polished flutes**.

Application:

For roughing milling with high demands on the component surface.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 202004.

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 22 mm

Overhang length L_1 incl. recess: 30 mm

Recess Ø D_1 : 9.2 mm

Overall length L: 72 mm

Shank Ø D_s : 10 mm

Technical description

| | |
|---|---------|
| No. of teeth Z | 3 |
| Corner chamfer width at 45° | 0.2 mm |
| Feed f_z for slot milling in short-chipping aluminium | 0.07 mm |

| | |
|---|--------------------------------------|
| Recess $\varnothing D_1$ | 9.2 mm |
| Shank form | HA |
| Cutting edge $\varnothing D_c$ | 10 mm |
| Feed f_z for side milling in short-chipping aluminium | 0.09 mm |
| Overhang length L_1 incl. recess | 30 mm |
| Shank $\varnothing D_s$ | 10 mm |
| Overall length L | 72 mm |
| Flute length L_c | 22 mm |
| Direction of infeed | horizontal, oblique and vertical |
| Shank | DIN 6535 HA to h6 |
| Tolerance nominal \varnothing | f8 |
| Balance quality with shank | G 2.5 with HA |
| Helix angle | 45 degrees |
| Corner chamfer angle | 45 degrees |
| Coating | ZOX |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | W |
| Helix angle characteristic | unequal spacing |
| Spacing of the cutters | unequal spacing |
| Cutting width a_e for milling operation | $0.5 \times D$ for side milling |
| Cutting width a_e for milling operation | Full slot cutting depth $1 \times D$ |
| Through-coolant | no |
| Machining strategy | HPC |
| Colour ring | yellow |
| Type of product | End mill |

Services

| | |
|------------------------|-------------|
| Shank recess Type FRST | 209900 FRST |
|------------------------|-------------|

Shank grinding Type HB

129100 HB