

## Garant

### Solid carbide milling cutter HPC, ZOx, Ø f8 DC: 8 mm



#### Order data

Order number	202251 8
GTIN	4045197538581
Item class	11X

#### Description

##### Version:

Sturdy roughing end mill **without** knuckle profile.

With strong core, **special chip breaker recesses** and **large polished flutes**.

##### Application:

For roughing milling with high demands on the component surface.

##### Note:

**NEW GENERATION AVAILABLE!**

**Recommended successor product is No. 202017.**

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length  $L_c$ : 13 mm

Overhang length  $L_1$  incl. recess: 62 mm

Recess Ø  $D_1$ : 7.4 mm

Overall length L: 100 mm

Shank Ø  $D_s$ : 8 mm

#### Technical description

Overhang length $L_1$ incl. recess	62 mm
Corner chamfer width at 45°	0.2 mm
Feed $f_z$ for slot milling in short-chipping aluminium	0.06 mm

No. of teeth Z	3
Feed $f_z$ for side milling in short-chipping aluminium	0.08 mm
Cutting edge $\varnothing D_c$	8 mm
Recess $\varnothing D_1$	7.4 mm
Shank form	HA
Shank $\varnothing D_s$	8 mm
Overall length L	100 mm
Flute length $L_c$	13 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HA to h6
Tolerance nominal $\varnothing$	f8
Balance quality with shank	G 2.5 with HA
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	ZOX
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	$0.3 \times D$ for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
------------------------	-------------

Shank grinding Type HB

129100 HB