

Garant

Solid carbide milling cutter with internal coolant supply HPC, ZOx, Ø f8 DC: 20 mm



Order data

Order number	202255 20
GTIN	4045197415134
Item class	11X

Description

Version:

Sturdy roughing end mill **without** knuckle profile.

With strong core, **special chip breaker recesses** and **large polished flutes**.

Application:

For roughing milling with high demands on the component surface.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 202006.

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c : 41 mm

Overhang length L_1 incl. recess: 52 mm

Recess Ø D_1 : 19 mm

Overall length L: 104 mm

Shank Ø D_s : 20 mm

Technical description

Recess Ø D_1	19 mm
Feed f_z for slot milling in short-chipping aluminium	0.12 mm

Shank form	HB
No. of teeth Z	3
Overhang length L_1 incl. recess	52 mm
Corner chamfer width at 45°	0.2 mm
Cutting edge $\varnothing D_c$	20 mm
Feed f_z for side milling in short-chipping aluminium	0.16 mm
Shank $\varnothing D_s$	20 mm
Overall length L	104 mm
Flute length L_c	41 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	f8
Balance quality with shank	G 2.5 with HB
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	ZOX
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank Ø tool 20 mm	SZ2025 20