

Garant

Solid carbide milling cutter with internal coolant supply HPC, ZOx, Ø f8 DC: 25 mm



Order data

Order number	202255 25
GTIN	4045197454515
Item class	11X

Description

Version:

Sturdy roughing end mill **without** knuckle profile.

With strong core, **special chip breaker recesses** and **large polished flutes**.

Application:

For roughing milling with high demands on the component surface.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 202006.

Tolerance nominal Ø: f8

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c : 52 mm

Overhang length L_1 incl. recess: 62 mm

Recess Ø D_1 : 24 mm

Overall length L: 121 mm

Shank Ø D_s : 25 mm

Technical description

No. of teeth Z	3
Feed f_z for slot milling in short-chipping aluminium	0.14 mm

Corner chamfer width at 45°	0.3 mm
Cutting edge $\varnothing D_c$	25 mm
Overhang length L_1 incl. recess	62 mm
Feed f_z for side milling in short-chipping aluminium	0.18 mm
Shank form	HB
Recess $\varnothing D_1$	24 mm
Shank $\varnothing D_s$	25 mm
Overall length L	121 mm
Flute length L_c	52 mm
Direction of infeed	horizontal, oblique and vertical
Shank	DIN 6535 HB to h6
Tolerance nominal \varnothing	f8
Balance quality with shank	G 2.5 with HB
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	ZOX
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST

209900 FRST