

Garant
Solid carbide milling cutter MTC, uncoated, Ø h6 DC: 20 mm

Order data

Order number	202257 20
GTIN	4045197860101
Item class	11X

Description
Version:

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

Without 45° corner chamfer.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 202012.

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c : 41 mm

Overhang length L_1 incl. recess: 74 mm

Recess Ø D_1 : 19 mm

Overall length L: 126 mm

Shank Ø D_s : 20 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Flute length L_c	41 mm

Balance quality with shank	G 2.5 with HB
Shank form	HB
No. of teeth Z	3
Feed f_z for side milling in short-chipping aluminium	0.12 mm
Tolerance nominal \varnothing	h6
Recess $\varnothing D_1$	19 mm
Overall length L	126 mm
Feed f_z for slot milling in short-chipping aluminium	0.085 mm
Shank $\varnothing D_s$	20 mm
Shank	DIN 6535 HB to h6
Overhang length L_1 incl. recess	74 mm
Cutting edge $\varnothing D_c$	20 mm
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm

SZ2025 20

