

## Garant

### Solid carbide milling cutter MTC, uncoated, Ø h6 DC: 8 mm



#### Order data

Order number	202257 8
GTIN	4045197860064
Item class	11X

#### Description

##### Version:

**Eccentric relief ground**, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium workpieces.

**Without** 45° corner chamfer.

##### Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

##### Note:

**NEW GENERATION AVAILABLE!**

**Recommended successor product is No. 202012.**

Tolerance nominal Ø: h6

No. of teeth Z: 3

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length  $L_c$ : 21 mm

Overhang length  $L_1$  incl. recess: 30 mm

Recess Ø  $D_1$ : 7.4 mm

Overall length L: 68 mm

Shank Ø  $D_s$ : 8 mm

#### Technical description

Balance quality with shank	G 2.5 with HA
Flute length $L_c$	21 mm

Overhang length $L_1$ incl. recess	30 mm
Cutting edge $\varnothing D_c$	8 mm
Tolerance nominal $\varnothing$	h6
Feed $f_z$ for side milling in short-chipping aluminium	0.04 mm
Shank $\varnothing D_s$	8 mm
Direction of infeed	horizontal, oblique and vertical
Recess $\varnothing D_1$	7.4 mm
Overall length L	68 mm
Shank form	HA
Feed $f_z$ for slot milling in short-chipping aluminium	0.03 mm
No. of teeth Z	3
Shank	DIN 6535 HA to h6
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Helix angle characteristic	unequal spacing
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------

