## Garant

## Solid carbide milling cutter MTC, DLC, Ø DC: 10M mm



## Order data

Order number	202270 10M
GTIN	4045197763945
Item class	11X

## Description

#### Version:

With the latest generation of **DLC coating sp**<sup>2</sup>.

**Eccentric relief ground**, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

#### Lengths similar to **DIN 6527 long.**

#### **Application:**

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres. **Note:** 

#### **NEW GENERATION AVAILABLE!**

#### Recommended successor products are No. 202004 and No. 202010.

Tolerance nominal  $\emptyset$ : h6 No. of teeth Z: 3 Helix angle: 45 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HA to h6 Balance quality with shank: G 2.5 with HA No. of teeth Z: 3 Flute length L<sub>c</sub>: 30 mm Overhang length L<sub>1</sub> incl. recess: 38 mm Recess  $\emptyset$  D<sub>1</sub>: 9.2 mm Overall length L: 80 mm Shank  $\emptyset$  D<sub>3</sub>: 10 mm

## **Technical description**

Overhang length L<sub>1</sub> incl. recess

38 mm

Overall length L	80 mm
Direction of infeed	horizontal, oblique and vertical
Shank form	HA
Balance quality with shank	G 2.5 with HA
Flute length L <sub>c</sub>	30 mm
Corner chamfer width at 45°	0.2 mm
Recess Ø D <sub>1</sub>	9.2 mm
Shank Ø Ds	10 mm
Feed $f_z$ for side milling in short-chipping aluminium	0.05 mm
Feed $f_z$ for slot milling in short-chipping aluminium	0.04 mm
Cutting edge Ø D <sub>c</sub>	10 mm
Shank	DIN 6535 HA to h6
No. of teeth Z	3
Tolerance nominal Ø	h6
Helix angle	45 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Туре	W
Helix angle characteristic	unequal spacing
Cutting width $a_e$ for milling operation	0.5×D for side milling
Cutting width $a_e$ for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	MTC
Colour ring	yellow
Type of product	End mill

# Services

Shank grinding Type HB

129100 HB